





Green Pin® Rotating Hoist Ring UNC GR8

Grade 8 rotating hoist ring UNC



ADAUNC



- **Material:** alloy steel, grade 8, quenched and tempered
- **Safety factor:** MBL equals 5 x WLL
- **Finish:** painted red or white
- **Temperature range:** -40°C up to +200°C
- **Certification:** 2.1 2.2 3.1 MPI b CE
- **Note:** WLL indicated hereunder are given in the worst conditions of use, i.e. 90°

working load limit	diameter thread	width inside	length inside	diameter	length	thickness base	width outside	diameter base	diameter base	length inside	hex key	torque value	weight each
t	a inch	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	j mm	mm	Nm	kg
0.4	⁵ / ₁₆ - 18UNC	35	41	13	18	35	68	34	38	43	6	6.5	0.43
0.6	³ / ₈ - 16UNC	35	39	13	18	37	68	34	38	43	8	13	0.44
1	¹ / ₂ - 13UNC	35	36	13	24	39	68	34	38	43	10	22	0.46
1.7	⁵ / ₈ - 11UNC	35	42	13	31	43	68	34	38	52	13	55	0.54
2.5	³ / ₄ - 10UNC	35	38	13	31	47	68	34	38	52	16	110	0.55
3.5	⁷ / ₈ - 9UNC	53	57	20	37	69	105	49	56	71	19	150	1.88
4.5	1 - 8UNC	53	55	20	43	71	105	49	56	71	19	190	1.93